

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification⁴ : A61B 10/00</p>	<p>A1</p>	<p>(11) International Publication Number: WO 86/ 04225 (43) International Publication Date: 31 July 1986 (31.07.86)</p>
<p>(21) International Application Number: PCT/US86/00060 (22) International Filing Date: 13 January 1986 (13.01.86) (31) Priority Application Number: 691,675 (32) Priority Date: 15 January 1985 (15.01.85) (33) Priority Country: US (71) Applicant: APPLIED BIOMETRICS, INC. [US/US]; 2879 Westedge Boulevard, Mound, MN 55364 (US). (72) Inventors: ABRAMS, Jerome, H. ; 248 Bedford Street S.E., Minneapolis, MN 55414 (US). HOVLAND, Claire, T. ; 2879 Westedge Boulevard, Mound, MN 55364 (US). (74) Agents: JOHNSON, Eugene, L. et al.; Dorsey & Whit- ney, 2200 First Bank Place East, Minneapolis, MN 55402 (US).</p>		<p>(81) Designated States: AT (European patent), BE (Euro- pean patent), CH (European patent), DE (European patent), FR (European patent), GB (European pa- tent), IT (European patent), JP, LU (European pa- tent), NL (European patent), SE (European patent). Published <i>With international search report.</i></p>

(54) Title: **METHOD AND APPARATUS FOR MEASURING ARTERIAL BLOOD FLOW**

(57) Abstract

Blood flow in the aorta and pulmonary artery of a mammal, most typically a human, is measured volumetrically by a non-invasive, ultrasound method and apparatus. The method comprises placing a piezoelectric ultrasound transducer in the trachea in great proximity to the aorta or pulmonary artery by passage through the oral or nasal cavity past the epiglottis and into the trachea or by passage through the surgical opening into the trachea in the case of patients who have had a tracheotomy. Ultrasound waves are transmitted toward the path of flow of blood in the artery. Reflected waves are received. The average Doppler frequency difference between transmitted and received waves is measured. The cross-sectional size of the artery is measured. Blood flow rate is determined from the measurements. The apparatus comprises a tracheal tube (11) or probe with one or two transducers (21, 22) mounted at one end of the tube. The transducer(s) is (are) disposed to transmit ultrasound in selected directions. Electrical conductors (24, 25, 26, 27) extend from the transducers the length of the probe.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GA	Gabon	MR	Mauritania
AU	Australia	GB	United Kingdom	MW	Malawi
BB	Barbados	HU	Hungary	NL	Netherlands
BE	Belgium	IT	Italy	NO	Norway
BG	Bulgaria	JP	Japan	RO	Romania
BR	Brazil	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	LI	Liechtenstein	SN	Senegal
CH	Switzerland	LK	Sri Lanka	SU	Soviet Union
CM	Cameroon	LU	Luxembourg	TD	Chad
DE	Germany, Federal Republic of	MC	Monaco	TG	Togo
DK	Denmark	MG	Madagascar	US	United States of America
FI	Finland	ML	Mali		
FR	France				